VOLT MODEL S

15" x 16" max print area, 21" x 28" max screen size

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
6/2	8'11"	1ph, 208 VAC, 16A 3ph, 208 VAC, 9A
6/3	8'11"	1ph, 208 VAC, 17A 3ph, 208 VAC, 10A
6/4	8'11"	1ph, 208 VAC, 18A 3ph, 208 VAC, 11A
6/5	8'11"	1ph, 208 VAC, 19A 3ph, 208 VAC, 12A

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
8/6	10'2"	1ph, 208 VAC, 20A 3ph, 208 VAC, 13A
8/7	10'2"	1ph, 208 VAC, 21A 3ph, 208 VAC, 14A
10/8	11'2"	1ph, 208 VAC, 31A 3ph, 208 VAC, 18A
10/9	11'2"	1ph, 208 VAC, 32A 3ph, 208 VAC, 19A

VOLT MODEL M

16" x 18" max print area, 23" x 33" max screen size

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
6/2	9'4"	1ph, 208 VAC, 16A 3ph, 208 VAC, 9A
6/3	9'4"	1ph, 208 VAC, 17A 3ph, 208 VAC, 10A
6/4	9'4"	1ph, 208 VAC, 18A 3ph, 208 VAC, 11A
6/5	9'4"	1ph, 208 VAC, 19A 3ph, 208 VAC, 12A
8/6	10'7"	1ph, 208 VAC, 20A 3ph, 208 VAC, 13A
8/7	10'7"	1ph, 208 VAC, 21A 3ph, 208 VAC, 14A

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
10/8	12'3"	1ph, 208 VAC, 31A 3ph, 208 VAC, 18A
10/9	12'3"	1ph, 208 VAC, 32A 3ph, 208 VAC, 19A
12/10	13'7"	1ph, 208 VAC, 36A 3ph, 208 VAC, 20A
12/11	13'7"	1ph, 208 VAC, 37A 3ph, 208 VAC, 21A
14/12	15'	3ph, 208 VAC, 23A

VOLT MODEL L

20" x 20" max print area, 26" x 36" max screen size

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
6/4	11'4"	1ph, 208 VAC, 18A 3ph, 208 VAC, 11A
6/5	11'4"	1ph, 208 VAC, 19A 3ph, 208 VAC, 12A
8/6	12'2"	1ph, 208 VAC, 20A 3ph, 208 VAC, 13A
8/7	12'2"	1ph, 208 VAC, 21A 3ph, 208 VAC, 14A
10/8	13'8"	1ph, 208 VAC, 31A 3ph, 208 VAC, 18A
10/9	13'8"	1ph, 208 VAC, 32A 3ph, 208 VAC, 19A

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
12/10	15'2"	1ph, 208 VAC, 36A 3ph, 208 VAC, 20A
12/11	15'2"	1ph, 208 VAC, 37A 3ph, 208 VAC, 21A
14/12	16'7"	3ph, 208 VAC, 23A
16/14	18'	3ph, 208 VAC, 32A
18/16	19'10"	3ph, 208 VAC, 36A
20/18	21'4"	3ph, 208 VAC, 38A

VOLT MODEL XL

20" x 28" max print area, 26" x 43" max screen size

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
8/6	13'6"	1ph, 208 VAC, 20A
-,-		3ph, 208 VAC, 13A
8/7	13'6"	1ph, 208 VAC, 21A
		3ph, 208 VAC, 14A
10/8	15'	1ph, 208 VAC, 31A
10/6		3ph, 208 VAC, 18A
10/9	15'	1ph, 208 VAC, 32A
		3ph, 208 VAC, 19A
12/10	16'6"	1ph, 208 VAC, 36A
		3ph, 208 VAC, 20A

STATIONS/COLORS	DIAMETER	POWER REQUIREMENT
12/11	16'6"	1ph, 208 VAC, 37A 3ph, 208 VAC, 21A
14/12	17'11"	3ph, 208 VAC, 23A
16/14	19'9"	3ph, 208 VAC, 32A
18/16	21'3"	3ph, 208 VAC, 36A
20/18	22'8"	3ph, 208 VAC, 38A



ANATOL EQUIPMENT MANUFACTURING CO

919 SHERWOOD DRIVE | LAKE BLUFF, IL 60044 | 1.847.367.9760 WWW.ANATOL.COM | SALES@ANATOL.COM





PROFESSIONAL GRADE ALL-ELECTRIC AUTOMATIC PRESS

Reliable and Long Lasting

- No pneumatic parts for years of reliable service
- No compressor or chiller required

Servo Electric Technology

- Extremely efficient
- Quiet Operation

Available in configurations of 6 stations/2 colors - 20 stations/18 colors Maximum print area of 20" x 28"





STANDARD FEATURES

CONTROL INTERFACE

- Aries OS User-friendly operating system
- 15" touchscreen with intuitive one-touch access to all job settings and machine functions for fast set-ups
- Swivel boom arm for easy access to each print head
- Easy access to operator's manual

FUNCTIONS

- Save all parameters of a stored job: off-contact, indexer speed, print head speed, print area, number of strokes, flash cure time and temperature, color design, mode
- Set pallet preheat temperature
- Quickly set the same speed and print distance for all heads

INDEXING SYSTEM

- Servo indexer allows for clockwise, counter-clockwise and half indexing
- Smooth and quiet indexing at high speeds
- Ball bearing lead screw design with internal lubrication system
- Free-wheel capabilities

PRINT HEADS

- AC electric-driven print heads enhance smoothness, speed and power
- Front and rear stroke adjustment
- Single-handed tool-less squeegee/flood bar locking

REGISTRATION

- True three-point micro-registration of screen (front-back, left-right, and rotational movement)
- Accepts a number of common pre-registration systems available on the market

CHANGE THE WAY YOU WORK

INCREASED EFFICIENCY. HIGHER PRODUCTIVITY.

Anatol's VOLT all-electric screen printing machine introduces "smart" technology that lets screen printers surpass the possibilities of traditional screen printing equipment.

What's a servo motor?

Unlike other automatic presses, the VOLT uses servo motors for power. It's a rotary actuator that allows for precise control of angular position, velocity and acceleration. In simple terms, these "smart" motors make your job easier by giving you a more efficient way of running your business.

The simplicity of servo motors is part of what makes them so reliable - often outlasting the life of the machine.

TWO-YEAR LIMITED WARRANTY

Every effort has been made to ensure the accuracy of the promotional information included in this brochure. Specifications are subject to change. Anatol Equipment Manufacturing Co. and its subsidiaries, if any, expressly disclaim any liability for damages, consequential or incidental, resulting from the purchase, transportation, installation, or use of any products based upon information contained within this brochure. Any rights or remedies are limited solely to those provided in writing by Anatol Equipment Manufacturing Co. at the time of sale.

PALLET SYSTEM

- Slide-style pallets
- Tool-free locking
- Precise four-point pallet leveling system
- 16" x 22" solid aluminum, low profile rubber-coated pallets

SKIP SHIRT & SMASH BUTTON

- Save time and supplies by preventing the press from printing on empty pallets with our Skip Shirt function on the control panel
- Smash button halts printing in the event of a shirt being loaded improperly

SAFETY SYSTEM

 Safety bars located between each print head and on each side of the load and unload station ensure safety during press set-up and operation

CENTRAL OFF-CONTACT

• Digitally-controlled central off-contact with 400 settings up to 2/5"

OPTIONS

- Rapid Wave Quartz Flash Cure
- Infrared Panel Shuttle Flash Cure
- Pallet locator for slide-style mounting pallets
- Foot Pedal Control
- Quick-release pallet system
- Special sizing available for doorways as small as 28"



